

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Dominique Nicolas Cade et al. Examiner: Not Assigned
Serial No.: Not Assigned Art Unit: Not Assigned
Filed: March 8, 2004
For: APPARATUS FOR AND METHOD OF SEALING CAPSULES
Date: March 8, 2004
Commissioner for Patents
P. O. Box 1450
Alexandria, VA 22313-1450


CLAIM OF PRIORITY and SUBMISSION OF CERTIFIED COPY

Sir:

Applicants hereby claim priority from European Patent application 03290723.0, filed March 21, 2003. Applicants are submitting an actual copy of the certified priority document with the filing of this application.

It is believed that no fee is due, however, if it is believed that a fee is due, please charge Deposit Account 23-0455.

Respectfully submitted,




Kenneth G. Lemke
Reg. No. 47,746

Dated: March 8, 2004
Warner-Lambert Company, LLC
201 Tabor Road
Morris Plains, New Jersey 07950
Phone 973 385-6243
Fax 973 385-3117
Customer No. 29668

CERTIFICATE OF MAILING PURSUANT TO 37 C.F.R. SECTION §1.10

I hereby certify that this Information Disclosure Statement and the documents referred to as enclosed herein are being deposited with the United States Postal Service, Express Mail Label No. EV104995212 on this March 8, 2004 date, in an envelope bearing "Express Mail Post Office" to Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.



Christine Avenoso

Apparatuspc25692a21804



**Europäisches
Patentamt**

**European
Patent Office**

**Office européen
des brevets**

Bescheinigung

Certificate

Attestation

Die angehefteten Unterla-
gen stimmen mit der
ursprünglich eingereichten
Fassung der auf dem näch-
sten Blatt bezeichneten
europäischen Patentanmel-
dung überein.

The attached documents
are exact copies of the
European patent application
described on the following
page, as originally filed.

Les documents fixés à
cette attestation sont
conformes à la version
initialement déposée de
la demande de brevet
européen spécifiée à la
page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

03290723.0

Der Präsident des Europäischen Patentamts;
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

R C van Dijk

THIS PAGE BLANK (USPTO)



Anmeldung Nr:
Application no.: 03290723.0
Demande no:

Anmeldetag:
Date of filing: 21.03.03
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

Warner-Lambert Company LLC
201 Tabor Road
Morris Plains,
New Jersey 07950
ETATS-UNIS D'AMERIQUE

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.
If no title is shown please refer to the description.
Si aucun titre n'est indiqué se référer à la description.)

Apparatus for and method of sealing capsules

In Anspruch genommene Priorität(en) / Priority(ies) claimed /Priorité(s)
revendiquée(s)
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/
Classification internationale des brevets:

A61J3/07

Anmeldetag benannte Vertragsstaaten/Contracting states designated at date of
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC
NL PT RO SE SI SK TR

THIS PAGE BLANK (USPTO)

Apparatus for and method of sealing capsules**Description**

This invention relates to a method of and apparatus for sealing capsules and to the capsule formed thereby.

5 The capsules sealed by the method and apparatus according to the present invention are hard shell, telescopically joined capsules with coaxial partly overlapping body parts. The capsules may be made of gelatin or of other materials whose properties are pharmaceutically acceptable with respect to their chemical and physical properties.

10 The problem to be solved with respect to such capsules as compared to other dosage forms is the fact that the coaxial body parts must be well sealed in order to avoid leaking of any content to the outside or contamination thereof. Further, tampering with the content of the capsule or the capsule as such should be evident and externally visible for safety proposes. Any technique of sealing the
15 capsules must be suitable for large scale bulk production to reduce manufacturing time and costs and to reduce waste due to imperfections of the product.

EP 0 116 743 A1, EP 0 116 744 A1 and EP 0 180 543 A1 disclose methods and devices for sealing such capsules having hard shell coaxial cap and body parts
20 which overlap when telescopically joined. The process employed comprises the steps of dipping batches of the capsules randomly oriented in mesh baskets or oriented with their cap parts upright into a sealing fluid making capillary action within the overlap of the cap and body parts or spraying the sealing fluid or steam thereof onto the seam of the overlap, removing the sealing fluid from the

surface of the capsules by an air blower, and applying thermal energy to the capsules while conveying the baskets through a dryer. The documents disclose the use of a wide range of sealing fluids and specific temperatures and modes of application of thermal energy, the disclosure of which is incorporated herein by reference.

EP 1 072 245 A1 also discloses a method for sealing telescopically joined capsules with coaxial body parts through subsequent application of a sealing liquid by the overlapping region at the joint between a cap and a body, the removal of excess sealing liquid, and the application of thermal energy for drying purposes. This document particularly describes the steps of applying a sealing liquid including a solvent uniformly to the external edge of the gap of a capsule to be sealed to form a liquid ring around the circumference of the capsule, removing excess sealing liquid from the exterior of the capsule and drying the capsule by applying thermal energy from outside while gently tumbling and conveying the capsule on a spiral path. Spray nozzles are used for individually applying the sealing liquid. The excess solution is removed from around the capsule by vacuum suction or air jets. The disclosure of this document is incorporated herein by reference, too.

The prior systems for sealing capsules are partly imperfect as regards the quality of the seal and the controllability of the process parameters influencing the quality of the seal.

The present invention aims at providing an improved method and apparatus for sealing telescopically joined capsules with coaxial partly overlapping body parts, through subsequent application of a sealing fluid and an improvement of the fluid injection phase in order to reach the maximum volume available in the overlap of the body parts while the capsule remains free of residual liquid on its surface.

With respect to this object the present invention provides a method and an apparatus for sealing telecopically joined capsules with coaxial partly overlapping body parts as defined in the appended claims. Sealing clamps are used to seal efficiently hard capsules. Filled or empty capsules are to be oriented before the sealing operation. The sealing clamps hold each capsule in a precise and reproducible upright position. A known quantity of sealing fluid is injected in the overlap of the body parts within a well-defined volume. The excess of sealing fluid is removed from the outside of the capsule shell. Moreover the excess of sealing fluid is removed from the sealing clamp to prevent build-up of sealing fluid. Finally the capsule is released properly.

The use of spray clamps instead of bushings or any other apparatus enables to limit the zone where the sealing fluid is injected to the overlap of the body parts. The design of the sealing clamp limits the location of the sealing fluid to the interior volume of the clamp. The excess of sealing fluid remaining in the clamp is recovered through suction channels.

Using a spray clamp also forces the capsules to be cylindrical which is an advantage when using flexible polymer material to manufacture capsule. Thus the capsule diameter is homogeneous on 360°. The penetration of the sealing liquid by the capillary effect on the whole capsule circumference is favoured. An additional benefit to use a sealing clamp is to guarantee an actual vertical positioning of the capsule with regard to the location of the sealing liquid injection hole.

The spray clamp can be composed of different parts. Each part will participate to the various steps of the process. As an example, the injection of the sealing liquid can happen in one part whilst the excess of sealing fluid can be collected in a second part.

The number of main functional parts that compose the spray clamp can vary from one to six. The number of injection ports can vary from one to eight. The number of suction ports can vary from one to ten. The number of airing can vary from one to six. The positioning of those parts can be spatially arranged to obtain the desired effect. One to three liquid recovery grooves can be added to the design of clamp.

In a preferred embodiment the sealing clamp consists of two parts. These two parts are joined together to open and close the sealing clamp.

The present invention will now be described in more detail, by way of example, with reference to the accompanying drawings in which the following figures show:

Fig. 1 first embodiment of a sealing clamp in open position in perspective view,

Fig. 2 sealing clamp of Fig. 1, closed, in cross section,

Fig. 3 second embodiment of a sealing clamp in open position in perspective view,

Fig. 4 sealing clamp of Fig. 3, closed, in cross section,

Fig. 5 third embodiment of a sealing clamp in open position in perspective view,

Fig. 6 sealing clamp of Fig. 5, closed, in cross section,

Fig. 7 forth embodiment of a sealing clamp in open position in perspective view,

Fig. 8 sealing clamp of Fig. 7, closed, in cross section,

Fig. 9 fifth embodiment of a sealing clamp in open position in perspective view,

Fig. 10 sealing clamp of Fig. 9, closed, in cross section,

Fig. 11 sixth embodiment of a sealing clamp in open position in perspective view,

Fig. 12 sealing clamp of Fig. 11, closed, in cross section,

Fig. 13 seventh embodiment of a sealing clamp in open position in perspective view,

Fig. 14 sealing clamp of Fig. 13, closed, in cross section.

10 Figure 1 and 2 show a first embodiment of a sealing clamp 1 consisting of a first part 2 and a second part 3. In the closed sealing clamp the edge of the cap of a capsule, not shown in the drawings, is precisely located between 0 and 2 mm above the injection port 5. The sealing fluid is injected via an injection port 5 located at 90° from the parting line of the first part 2. Air or any other gas can
15 flow through an airing 6 located at 45° from the parting line of the first part 2 and two suction ports 7 located at 90° and 60° from the parting line of the second part 3. The injection port 5 and the airing 6 are located between 0 and 2 mm below the cap edge while the two suction ports 7 are in the liquid recovery groove 8.

20 The difference between the first embodiment of a sealing clamp in figure 1 and 2 and the other embodiments shown in figure 3 to 14 consists in the number and position of injection ports 5, airings 6, suction ports 7 and liquid recovery grooves 8. The embodiments one to four of figures 1 to 8 enable sealing of 20 to 50 % of the maximum surface available. With the sealing clamp of embodiment
25 five a sealed surface of 80 % is reached. Use of the sealing clamp of embodiment six gives a large sealed zone of 90 to 100 %. With the sealing

clamp of embodiment seven the total removal of the excess of sealing fluid from the capsule shell is possible preventing subsequent process defects.

A second embodiment of a sealing clamp 11 shown in figure 3 and 4 consists of a first part 12 and a second part 13. In the closed sealing clamp the edge of the cap of a capsule, not shown in the drawings, is precisely located between 0 and 2 mm above the injection port 15. The sealing fluid is injected via an injection port 15 located at 90° from the parting line of the first part 12. Air or any other gas can flow through an airing 16 located at 75° from the parting line of the first part 12 and two suction ports 17 located at 90° and 60° from the parting line of the second part 13. The injection port 15 is located between 0 and 2 mm below the edge of the cap of a capsule while the airing 16 and the two suction ports 17 are in the liquid recovery groove 18.

A third embodiment of a sealing clamp 21 shown in figure 5 and 6 consists of a first part 22 and a second part 23. In the closed sealing clamp the edge of the cap of a capsule, not shown in the drawings, is at the bottom 29 of the liquid recovery groove 28. The sealing fluid is injected via an injection port 25 located at 90° from the parting line of the first part 22 in the liquid recovery groove 28. Air or any other gas can flow through an airing 26 located at 45° from the parting line of the first part 22 and two suction ports 27 located at 90° and 60° from the parting line of the second part 23. The airing 26 and the two suction ports 27 are located in the liquid recovery groove 28.

A forth embodiment of a sealing clamp 31 shown in figure 7 and 8 consists of a first part 32 and a second part 33. In the closed sealing clamp the edge of the cap of a capsule, not shown in the drawings, is at the bottom 34 of the liquid recovery groove 38. The sealing fluid is injected via an injection port 35 located at 90° from the parting line of the first part 32 in the liquid recovery groove 38. Air or any other gas can flow through an airing 36 located at 45° from the parting line of the first part 32 and two suction ports 37 located at 90° and 60° from the

parting line of the second part 33. The airing 36 and the two suction ports 37 are located in the liquid recovery groove 38. Additional features are an absorbent layer 39 and a vertical rubber coating 40 at the bottom of the sealing clamp 31.

5 A fifth embodiment of a sealing clamp 41 shown in figure 9 and 10 consists of a first part 42 and a second part 43. In the closed sealing clamp the edge of the cap of a capsule, not shown in the drawings, is at the bottom 50 of a liquid injection groove 49 of the sealing clamp 41. The sealing fluid is injected via two injection ports 45 located at 60° from the parting line of the first part 42 and at 60° from the parting line of the second part 43. Both injection ports 45 enter into
10 a liquid injection groove 49. Air or any other gas can flow through two airings 46 located at 30° from the parting line of the first part 42 and of the second part 43 and through four suction ports 47 located at 90° and 120° from the parting line of the first part 42 and of the second part 43. The airings 46 and the suction ports 47 are located in the liquid recovery groove 48.

15 A sixth embodiment of a sealing clamp 51 shown in figure 11 and 12 consists of a first part 52 and a second part 53. In the closed sealing clamp the edge of the cap of a capsule, not shown in the drawings, is precisely located between 0 and 2 mm above the injection port 55. The sealing fluid is injected via an injection port 55 located at 60° from the parting line of the first part 52. Air or any other
20 gas can flow through an airing 56 located at 90° from the parting line of the first part 52 and a suction port 57 located at 120° from the parting line of the second part 53. The airing 56 and the suction port 57 are in the liquid recovery groove 58.

25 A seventh embodiment of a sealing clamp 61 shown in figure 13 and 14 consists of a first part 62 and a second part 63. In the closed sealing clamp the edge of the cap of a capsule, not shown in the drawings, is at the bottom 70 of a liquid injection groove 69 of the sealing clamp 61. The sealing fluid is injected via two injection ports 65 located at 135° from the parting line of the first part 62 and at

135° from the parting line of the second part 63. Both injection ports 65 enter into a liquid injection groove 69. Air or any other gas can flow through two airings 66 located at 150° from the parting line of the first part 62 and of the second part 63 and through four suction ports 67 located at 30° and 60° from the parting line of the first part 62 and of the second part 63. The airings 66 and the suction ports 67 are located in the liquid recovery groove 68.

Claims

1. A method of sealing a hard shell capsule having coaxial body parts which overlap when telescopically joined, which method comprises the steps of holding the capsule in a precise and upright position,
5 injecting a known quantity of sealing fluid in the overlap of the body parts, releasing the capsule.
2. Method according to claim 1, characterised in that the excess of sealing fluid is removed from the outside of the capsule shell.
3. Method according to claim 1 or 2, characterised in that the excess of
10 sealing fluid is removed from a clamp holding the capsule in the upright position.
4. An apparatus for sealing a hard shell capsule having coaxial body parts which overlap when telescopically joined, the apparatus comprising
15 a sealing clamp (1, 11, 21, 31, 41, 51, 61) to hold the capsule in an upright position and means (5, 15, 25, 35, 45, 55, 65) to inject the sealing fluid in the overlap of cap and body part.
5. An apparatus according to claim 4, characterised in that the means to
20 inject the sealing fluid are injection ports (5, 15, 25, 35, 45, 55, 65) in the sealing clamp (1, 11, 21, 31, 41, 51, 61).
6. An apparatus according to claim 4, characterised in that the sealing clamp has liquid recovery grooves (8, 18, 28, 38, 48, 58, 68).

7. An apparatus according to claim 4, characterised in that the sealing clamp has airing (6, 16, 26, 36, 46, 56, 66) and suction ports (7, 17, 27, 37, 47, 57, 67).
8. An apparatus according to claim 4, characterised in that the sealing clamp has a liquid injection groove (49, 69).




Abstract

A method is disclosed for the sealing of hard shell capsules having coaxial body parts which overlap when telescopically joined. Also described is an apparatus to seal the capsules.

- 5 The method comprises the steps of holding the capsule in a precise and upright position and injecting a known quantity of sealing fluid in the overlap of the body parts.

10 An apparatus for performing the method is also disclosed. The apparatus comprises a sealing clamp (1, 11, 21, 31, 41, 51, 61) to hold the capsule in an upright position and means (5, 15, 25, 35, 45, 55, 65) to inject the sealing fluid in the overlap of the body parts.

THIS PAGE BLANK (USPT






Fig. 5

Fig. 6




Fig. 7

Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14